

- Wide range of models
- High efficiency >96%
- Overheating protection
- Polarity protection
- **Current limited**
- Short-circuit protection
- Safe to use
- Easy to install
- Small and comapct
- User friendly
- DIN mount (option)
- Galvanic isolated



























DC-DC CONVERTER

Primepower DC-DC Converter is designed with the latest switching technology in DC to DC conversion. This brings an efficiency with over 96%. This brings a cool runing product with minimal powerloss.

The internal electronics is protected against wrong polarization and short-circuit which prevents damage to the device by misuse.

The standard enclosure is IP 21 with protective coating on the electronics.

All models have and ON/OFF function for remote use.









PRIMEPOWER DC-DC CONVERTER

- Wide range of models
- High efficiency >96%
- Overheating protection
- Polarity protection
- Current limited
- Short-circuit protection
- Safe to use
- Easy to install
- Small and compact
- User friendly
- DIN mount (option)
- Galvanic isolated

SPECIFICATION AND MODELS

| MODEL | 12-12 | 12-12 | 12-24 | 24-12 | 24-12 | 24-24 | 24-24 | 48-12 | 48-24 |
|---------------------------|----------------|----------------|----------------|----------------|----------------|----------------|----------------|----------------|----------------|
| ARTICLE | 60300 | 60310 | 60311 | 60303 | 60312 | 60304 | 60313 | 60332 | 60333 |
| INPUT | 9-18V | 9-18V | 9-18V | 18-36V | 18-36V | 18-36V | 18-36V | 33-65V | 33-65V |
| ОИТРИТ | 12V | 12V | 24V | 12V | 12V | 24V | 24V | 12V | 24V |
| POWER | 100W | 200W | 200W | 100W | 200W | 100W | 200W | 200W | 200W |
| ENCLOSURE | IP21 |
| CONNECTIONS | 6,3mm Faston |
| WEIGHT | 200g | 215g | 215g | 200g | 215g | 200g | 215g | 215g | 215g |
| MEASUREMENTS L x W x H | 115 x 88 x 9mm |

ALL MODELS HAVE AN EFFICIENCY OF >96% AND ON/OFF FUNCTION



