

CHARGER

DC-DC 9-32V DC 25A

- > **IP66 COMPLIANT**
- > **INPUT RANGE 9-32V**
- > **SAVES SPACE**



DC-DC 9-32V DC 25A CHARGER IN COMPACT DESIGN AND WITH DIRECT INPUT FROM SOLAR PANEL

This small and compact DC-DC charger complies with IP66 and can be programmed to charge STD, GEL, AGM, Calcium and LiFePO4 batteries.

It is compatible with SMART generators and has both over and under voltage protection as well as reverse polarity protection.

The charger can also be ideal in vehicles with 24V, which need 12V DC charging of a battery. It is also suitable for electric cars, where you want to put as little strain on the driveline as possible.

The DC-DC 9-32V DC 25A charger takes up very little space and can easily be hidden away under a seat or in the boot of the car, and it can withstand a harsh environment and temperatures between -20° and up to +80°.

> FEATURES

- DC/DC battery charger
- Silent for quiet operation
- Ignition and built-in MPPT (MPPT: ready for solar panels).

CHARGER

DC-DC 9-32V DC 25A

> SPECIFICATIONS

MODEL	AW019625A
INPUT VOLTAGE	230V AC
OUTPUT VOLTAGE	12V DC
OUTPUT POWER	
COMPATIBLE BATTERY TYPES	12V STD GEL AGM CAL LiFePO4
DIODE ON/OFF	Yes
OPERATING TEMPERATURE	-20 to +80°C
WEIGHT	1.85 kg
DIMENSIONS	151*121*44 mm (H*L*W)
DANGEROUS GOODS	No
CERTIFICATIONS	IP66

CONTACT INFORMATION

+45 56 56 54 00

mail@awilco.dk

awilco.dk

AWILCO ApS
Yderholmvej 64
4623 Ll. Skensved
Denmark